

3/4" FILLET OF PM SEALANT
 -ALLOW TO CURE FOR 2 HOURS BEFORE DETAIL STRIP APPLICATION


- PRIMETAK PRIMER
- PRIMETAK
- E.DRAIN ADHESIVE
- E.DRAIN 6000
- PRIMETAK DETAIL STRIP (12")

BENTOTAK
 (1 1/4" MIN. CONCRETE COVER FROM EDGE OF WALL AND IN BETWEEN STRIPS)

NOTE:
 DO NOT APPLY PRIMETAK PRIMER UNDER PM SEALANT

G:\My Drive\Epro Master Folder\Drafting\Details\Decks\Primetak\55.471.1 DECK ASSEMBLY - NON-HYDROSTATIC - TERMINATION WITH PLANTER CAPSTONE.dwg [Detail] April 27, 2021 - 9:14am

DECK ASSEMBLY - NON-HYDROSTATIC - TERMINATION WITH PLANTER CAPSTONE

	SYSTEM NAME	DRAWING NUMBER	<h1>PRIMETAK</h1>
	PRIMETAK	55.471.1	
	DRAFTER	DATE	
	RJT	2/23/2021	

AS A SUPPLIER OF FINISHED PRODUCTS ONLY, EPRO SERVICES, INC. DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN, ENGINEERING OR DIMENSIONS. THE PROJECT TEAM MUST VERIFY ALL DIMENSIONS AND SUITABILITY OF DETAILS. THE PRODUCTS LISTED ARE TRADEMARKS OF EPRO SERVICES, INC.