



3/4" FILLET OF PM SEALANT
 -ALLOW TO CURE FOR 2
 HOURS BEFORE DETAIL
 STRIP APPLICATION

BENTOTAK
 (1 1/4" MIN. CONCRETE
 COVER FROM EDGE OF WALL
 AND IN BETWEEN STRIPS)

NOTE:
 DO NOT APPLY PRIMETAK PRIMER UNDER PM SEALANT

G:\My Drive\Epro Master Folder\Drafting\Details\Decks\Primetak\55.471.2.2 DECK ASSEMBLY - NON-HYDROSTATIC - TERMINATION WITH REINFORCED PLANTER CAPSTONE (OPTION 2).dwg [Detail] April 27, 2021 - 9:07am

DECK ASSEMBLY - NON-HYDROSTATIC - TERMINATION WITH REINFORCED PLANTER CAPSTONE (OPTION 2)

	SYSTEM NAME	DRAWING NUMBER	
	PRIMETAK	55.471.2.2	
	DRAFTER	DATE	
	RJT	3/23/2021	

AS A SUPPLIER OF FINISHED RPRODUCTS ONLY, EPRO SERVICES, INC. DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN, ENGINEERING OR DIMENSIONS. THE PROJECT TEAM MUST VERIFY ALL DIMENSIONS AND SUITABILITY OF DETAILS. THE PRODUCTS LISTED ARE TRADEMARKS OF EPRO SERVICES, INC.