



NovaTape D

Product Description

Basic Use: NovaTape D is a double-sided butyl adhesive seaming tape that is used for detailing, sandwich lap seams, and patching the NovaTak membrane. NovaTape D's butyl adhesive forms an integral bond to the NovaTak butyl membrane that rivals the strength of heat welded seams while maintaining the flexibility of a butyl rubber membrane.

Composition: NovaTape D is a 40-mil (1 mm) unreinforced black butyl adhesive tape that is covered with a brown release liner.

Benefits

- NovaTape D creates butyl-to-butyl bonded seams that rival heat welded seams and prevent lateral water migration.
- NovaTape D is flexible, making it easy to apply for seaming, detailing, and membrane repairs.
- NovaTape D stays flexible in the extreme cold and prevents slumping in high heat.

Limitations

- NovaTape D rolls will absorb heat and become very warm to the touch.
- Application surface must be dry and free of dirt and debris.

Technical Data

Properties: See physical properties table.

Coverages: One roll covers 100 linear feet (30.5 linear meters), not including overlaps or waste.

Storage and Handling: Store raised off the floor away from sun and moisture, between 40-90°F (5-32°C).

Specification Writer: Contact EPRO before writing specifications on this product. NovaTak Butyl Pre-Applied Waterproofing System should be reviewed in order to meet project specific site conditions.

Installation

Preparation: Please refer to manufacturer's specifications for substrate requirements. Rolls should be inspected for cosmetic damage prior to application.

Application: Please refer to manufacturer's specifications.

Substrate Preparation: Wipe substrates to receive NovaTape D clean to remove any dirt, dust, or moisture. Clean the surface of penetrations or protrusions with a wire brush to remove dirt, dust, rust, and loose particles.

Installation: Unroll the NovaTape D and adhere the butyl adhesive surface to the NovaTak membrane or penetration. The release liner protected top surface of the tape should face toward the concrete pour. Line the top sheet or patch over the tape and adhere to the tape by removing the release liner and then use a heavy roller to maximize adhesion. Ensure the

release liner is removed from all areas of the applied NovaTape D prior to the concrete pour.

Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators (www.eproinc.com).

Roll Size: 40 mil (1 mm), 4" x 100' (120 mm x 30.5 m), 12.5 lbs (5.7 kg)
Box Size: 2 rolls, 25 lbs (11.4 kg)

Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

Equipment

Seaming: 4" heavy seam roller.

Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or www.eproinc.com.

This product was formally known as QMQ Dual Bond Plus and QMQ Dual Bond by Kingfield Construction Products.