



e.adhesive

Product Description

Basic Use: e.adhesive is designed as a surface adhesion promoter for wide range of substrates when a fast drying, solvent free, a tacky surface is required. Primarily used as a primer for EPRO waterstops, including e.stop b and e.stop hpl, e.adhesive is applied directly to concrete to provide a tacky substrate to secure e.stop in place prior to fastening of the waterstop.

Composition: e.adhesive is a high tack acrylic emulsion primer available in 1 gallon pails.

Benefits

- Quick drying
- Water based, environmentally friendly low VOC
- Tacky film provides strong adhesion to desired substrate
- Easily applied with brush or roller

Limitations

- Not to be applied over standing water or loose substrates
- Keep from freezing

Technical Data

Physical Properties:

Color:	White
Solids Content:	63+/- @5 by weight
Flammability:	Wet nonflammable, dry burns
Flash Point:	Greater than 212°F
Viscosity:	3,000 - 5,000 cps
VOC:	< 25 grams per liter

Coverages: 100 - 150 sq. ft. per gallon

Specification Writer: For e.stop applications, e.adhesive is required for all waterstop applications. One row of e.stop shall be used above the water table, and two rows are required for application elevations located in the design water table.

Installation

Preparation: All surfaces must be clean and free from debris, loose materials, curing agents, or any material that may interfere with the bond between e.adhesive and the substrate.

Application: Mix material before use to ensure uniformity. When applying with a brush, apply with a wide fiber brush to create a smooth uniform film. When applying with a roller, use a low nap phenolic core roller.

Drying Time: Initial set time is 30 min at 68°F

Application Temperature: 32°F - 110°F, for temperatures below freezing contact EPRO about acceptable surface conditioner.

Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators (www.eproinc.com).

Pail: 1 gallon, 10 pounds.

Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

Equipment

Brush or phenolic core roller should be used for application.

Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or www.eproinc.com.

This product replaces e.stop primer.