




e.drain 9000



Product Description

Basic Use: e.drain 9000 is applied in horizontal above grade waterproofing applications over plaza decks, planters, green roofs, and balconies. e.drain 9000 prefabricated drainage composite is designed to protect the E.Series system assembly, while effectively eliminating the buildup and ponding of water against the membrane assembly.

Composition: e.drain 9000 features a lightweight three-dimensional, high-compressive strength polypropylene core and bonded woven geotextile fabric. The bonded filter fabric allows water to pass freely into the molded drain while preventing soil particles from entering and clogging the core structure.

Benefits

- Provides extremely high compressive strength to meet a wide variety of project conditions
- Woven geotextile retains soil and sand while allowing filtered water to pass into drainage core
- Maintains flexibility in freezing temperatures

Limitations

- Long-term UV exposure is not recommended

Technical Data

Properties: See physical properties table

Coverages: 6' x 50' roll covers 300 square feet, not including overlaps or waste.

Specification Writer: Contact EPRO before writing specifications on this product. E.Series system assemblies should be reviewed in order to meet project specific site conditions.

Installation

Preparation: Please refer to manufacturer's specifications for substrate requirements. Rolls should be inspected for cosmetic damage prior to application. Substrate must be inspected prior to application to make certain it is in accordance with manufacturer's requirements.

Application: Please refer to manufacturer's specifications. Drainage panels may run horizontally or vertically. In blindside shoring applications, secure e.drain to shoring using 2-inch flat washer fasteners every 24 inches on center on seams and terminations and a minimum of every 48 inches on center in the field.

Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators (www.eproinc.com). 4' and 8' rolls are also available.

Roll: 6' x 50', 75 lbs.

Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

Equipment

Secure with shot pins using power-actuated fastener or by hand.

Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or www.eproinc.com.

This product was formally known as Ecodrain-S9000.



e.drain 9000

Typical Physical Properties

Physical Property	Test Method	Value
Dimpled Core		
Core Material		Polypropylene
Color		Black
Dimple Height.....	ASTM D 1777.....	0.4" (10.16mm)
Compressive Strength	ASTM D 6364.....	21,000 psf (1005 kN/m ²)
Flow rate.....	ASTM 4716	23 g/min/ft
Filter Fabric		
Grab Tensile.....	ASTM D 4632.....	370x250 lbs
CBR Puncture Resistance.....	ASTM D 6241.....	850 lbs
Apparent Operating Size	ASTM D 4751.....	40 sieve size (.42mm)
Water Flow Rate	ASTM D 4491.....	60 gpm/ft ² (2460 l/min/m ²)

Dimensions: 4' x 50', 6' x 50', 8' x 50'

Weight: 4' roll = 50 lbs, 6' rolls = 75 lbs, 8' rolls = 100 lbs